



Devoran Garden Gables, Unit 1, Greenbank Road, Devoran, Truro, Cornwall TR5 6PQ
Email: sales@devoran-garden-gables.co.uk
Website: www.devoran-garden-gables.co.uk
Phone: 01872 863376
Fax: 01872 863123

STANDARD INSTALLATION

INSTALLATION GUIDE FOR DEVORAN GARDEN GABLES

COVERING

LACING WIRE - Supplied as standard on gables with fix at joints.

Adjacent panels are joined together by a continuous lacing wire, ensuring in and out of mesh mesh. As the wire is inserted in and out of the mesh it is pulled in the direction of weaving, which then forms a tight joint.

All vertical joints and horizontal joints are to be laced. At the start and finish of the run of lacing, the wire should be wrapped around the panel wire 3 times.

It is recommended that the maximum length to be laced is approximately 1m. This requires about 1 cube of wire. The large coils of lacing wire supplied can be cut on one side of the coil which should give sufficient length for fix-offering. For run out of coils, as longer lengths of wire are needed for internal lacing.



HELICAL - Helicals are available at an additional cost for standard gable 3D system. Please enquire.

Adjacent panels are joined together by winding the helical down the mesh. Only use one helical for assembly when joining to an adjacent unit.

At the top and bottom end of the helical, the last coil must be turned vertically through 90 degrees to prevent the helical from moving.



C WINGS - Supplied at an additional cost. They can be used for all joining of units.

C wings are closed with a pneumatic closing tool. The pneumatic tool has to be purchased and therefore is mainly used only on larger schemes.

C wings must be fixed every other mesh space on all joints.

